



#### **Material Safety Data Sheet**

(Reproduce locally)

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910 1200. Standard must be consulted for specific requirements.

#### U.S. Department of Labor

Occupational Safety and Health Administration (Non-Mandatory Form)
Form Approved

OSHA 174 Sept. 1985

OMB No. 1218-0072 IDENTITY (as Used on Label and List) Note: Blank spaces are not permitted. If any item is not Nitrile N188-70 and N188-70W (white color) applicable or no information is available, the space must be marked to indicate that. Section I **Emergency Telephone Number** Manufacturer's name **Specification Seals Company** 714-777-5995 Address (Number, Street, City, State and ZIP Code) Telephone Number for Information 714-777-5995 4990 Hunter Ave Date Prepared Anaheim, CA 92807 Signature of Preparer (optional) Section II—Hazardous Ingredients/Identity Information Hazardous Components (Specific Chemical Identity, Common Name(s)) Other Limits ACGIH TLV OSHA PEL Recommended % (optional) Cured rubber O-Rings are not regarded as an article by definition of CFR 1910.1200 Paragraph (c) and provisions of CFR 1910.1200 do not apply. Section III-Physical/Chemical Characteristics Boiling Point Specific Gravity (H<sub>2</sub>0 = 1) N/A Melting Point Vapor Pressure (mm Hg) N/A N/A Evaporation Rate (Butyl Acetate = 1) Vapor Density (AIR = 1) N/A N/A Solubility in Water Insoluble Appearance and Odor Section IV—Fire and Explosion Hazard Data Flammable Limits UEL Flash Point (Method Used) LΕL N/A N/A N/A N/A Extinguishing Media Water, foam dry chemical Special Fire Fighting Procedures Do not enter confined fire space without proper protective equipment including NIOSH approved self contained breathing apparatus. Unusual Fire and Explosion Hazards not known

Section V—Reactivity Data Stability	Unstable N/A	T	Conditions to Avoid		
···· <b>,</b>	Stable N/A	1			
ncompatibility (Materials to Avoid)	IV/A	<u> </u>			
	N/A				
lazardous Decomposition or Byprod					
Carbon Monoxide, Carb		en Chloride, H		, Aliphatics, others possible	
Hazardous Polymerization	May Occur		Conditions to Avoid		
	Will Not Occur XXX				
Section VI—Health Hazard Dat		<u> </u>			
Route(s) of Entry	Inhalation? Skin			Ingestion?	
•	N/A	N/A		N/A	
Health Hazards (Acute and Chronic)	N/A	1477		· · · · · · · · · · · · · · · · · · ·	
	IVA				
		II DO N		0014 D	
Carcinogenicity	NTP?		onographs?	OSHA Regulated?	
	Not listed	Not I	isted	Not listed	
Signs and Symptoms of Exposure	N/A				
Medical Conditions					
Generally Aggravated by Exposure	N/A		• "		
Emergency and First Aid Procedures	N/A				
Section VII—Precautions for S	afe Handling and Use				
Steps to Be Taken in Case Material I	s Released or Spilled N/	Ά	•		
Waste Disposal Method Not ba					
regulations.	zardous by 40CFR2	61. Disposal	according to Fe	deral, State or Local	
Precautions to Be Taken in Handling	and Storing N/A				
Other Precautions				· · · · · · · · · · · · · · · · · · ·	
Contact of this product	with hot metal surfa	ices or other e	ievated sources	may produce irritating	
and/or noxious					
Fumes.					
Section VII—Control Measures Respiratory Protection (Specify Type					
			I Special		
entilation Local Exhaust N/A			Special N/A		
Mechanical (Genera	<sup>0</sup> N/A		Other N/A		
Protective Gloves Not normal	ly necessary	Eye Pro	olection Not norma	illy necessary	
Other Protective Clothing or Equipme	ent N/A	1			
Work/Hygienic Practices N/A					









COMPOUND

SHAPED BY DEBIGNY

4990 E. Hunter Avenue Anaheim, CA 92807 Ph. (800) 633-1155 Fax: (714) 777-6722 www.orings.com

3/11/08

Kent Systems 552 N. 66<sup>th</sup> Street Loveland, CO 80538

Attn: Holly Frost

Re: SPEC SEALS N100-70, N168-60, N188-60/W and N188-70/W compounds

Dear Holly,

Thank you for your inquiry about our above compounds. SPEC SEALS compounds have proven themselves in the field for over 20 years and meet a broad range of ASTM, FDA (with our N168-60, N188-60/W and N188-70/W compounds) and commercial specifications.

Per your inquiry, the above compounds do not use any of the following as ingredients per restricted substance requirements:

Lead

Mercury

Cadmium

Hexavalent chromium

Polybrominated biphenyls

Polybromited diphenyl ethers

Lead Chromate

Barium (Soluble)

Octabrominated diphenyl ether (OBDE)

Polybrominated biphenyl oxides (PBBO)

Polybrominated diphenyl oxides (PBDO)

Please let me know if you have any further questions about this or any other compound formulation issues.

Sincerely,

Craig Webb

Director of Business Development



### **Chemical Compatibility Information**

#### **Chemical Compatibility**

Our products are leak tested before they are shipped, so you should never find one of our products to leak. If you ever find that one of our products is leaking, chances are you are looking at a chemical compatibility issue. Don't worry, this is an issue that we can solve with a little testing and your help.

The first thing to keep in mind is that you should test every chemical you plan to use with the product. The fact that water worked fine in the first test, has little relevance to the acid that you actually intend to use.

Next, know what to look for. If you find that the couplings are harder to connect then they have been in the past, you might be looking at a chemical compatibility issue. In an extreme case, if you find that the Shut-Off valves "Freeze" open, then you are very likely looking at a chemical issue. No, the products are not designed to work that way, and no it is not a flaw in the product design. What is happening is, at least one of the materials is swelling from the chemical, and because of the close tolerance of our products, the valve is clamped open. Again, this is easily solved with a little testing.

Don't be afraid to talk to us about any issues that you may have, in most cases we can easily solve it. After all, we have a very good idea what we are doing here.


The table listed below is a good place to start your testing. If you see that any of the chemicals are listed as less then good, you may need a different material then what is on our standard products. Go ahead, call us at 970.593.3185 so that we can lend you a hand. Because we offer semi-custom options, we can help you figure out what you need.

OK now the legal stuff. The data presented in this table is for reference only. We recommend that you obtain Free Samples of our products for your testing. All information is supplied without expressed or implied warranty and does not constitute an endorsement.

Keep in mind that different products will have materials in them. Quick couplings have a number of different materials and are some times not visible when looking at the product. Be sure to test properly test your products before use.

We specialize in solutions and can solve most chemical issues






#### **Quick Coupling Chemical Compatibility Symptoms**

- Hard Connection or Disconnection
- Valve "Freezing"
- Leaking from the Coupling
- Leaking from the Valve

### Fitting Materials



#### **Tube Fitting Chemical Compatibility Symptoms**

- Product Becoming Softer
- Leaking From Side Wall
- Leaking around barb

Phone: 970.593.3185 > Fax: 970.593.9684 > www.KentSystems.com



## Chimical Compatibility Information (Plastic Materials)

CHEMICAL	NYLON	ACETAL	POLYPROPYLENE	POLYCARBONATE	PVDF (KYNAR®)
Acetic Acid	Severe Effect	Severe Effect	B-Good	B-Good	C-Fair
Acetone	Excellent	Excellent	A-Excellent	D-Severe Effect	D-Severe Effect
Acetylene	Excellent	Excellent	A-Excellent	D-Severe Effect	A-Excellent
Alcohols:Amyl	Excellent	Excellent	B-Good	B-Good	A-Excellent
Alcohols:Benzyl	Good	Excellent	A-Excellent	N/A	A-Excellent
Alcohols:Butyl	Severe Effect	Excellent	A-Excellent	A-Excellent	A-Excellent
Alcohols:Diacetone	Excellent	Excellent	B-Good	N/A	A-Excellent
Alcohols:Ethyl	Excellent	Excellent	A-Excellent	B-Good	N/A
Alcohols:Hexyl	Excellent	Excellent	N/A	N/A	N/A
Alcohols:Isobutyl	Excellent	Excellent	A-Excellent	N/A	N/A
Alcohols:Isopropyl	Severe Effect	Excellent	A-Excellent	A-Excellent	N/A
Alcohols:Methyl	Good	Excellent	A-Excellent	B-Good	A-Excellent
Alcohols:Octyl	Excellent	Excellent	N/A	N/A	N/A
Alcohols:Propyl	Severe Effect	Excellent	A-Excellent	N/A	A-Excellent
Aluminum Hydroxide	Excellent	Excellent	A-Excellent	B-Good	A-Excellent
Antifreeze	Severe Effect	Severe Effect	D-Severe Effect	N/A	N/A
Barium Sulfate	Excellent	Good	B-Good	D-Severe Effect	A-Excellent
Benzene Benzene	Excellent	Excellent	D-Severe Effect	D-Severe Effect	A-Excellent
Benzoic Acid	Severe Effect	Good	B-Good	B-Good	A-Excellent
Brewery Slop	N/A	Good	N/A	N/A	N/A
Butter	N/A	Excellent	N/A	N/A	N/A
Buttermilk	Good	Excellent	A-Excellent	A-Excellent	N/A
Cane Juice	Excellent	Excellent	C-Fair	N/A	A-Excellent
Carbon Dioxide (dry)	Excellent	Excellent	A-Excellent	N/A	A-Excellent
Carbon Monoxide	Excellent	Excellent	A-Excellent	N/A	B-Good
Carbon Tetrachloride	Severe Effect	Good	D-Severe Effect	D-Severe Effect	A-Excellent
Catsup	Excellent	Good	A-Excellent	N/A	N/A
Chlorine (dry)	Severe Effect	Severe Effect	D-Severe Effect	N/A	A-Excellent
Chlorine Water	Fair	Severe Effect	D-Severe Effect	N/A	B-Good
Chlorobenzene (Mono)	Severe Effect	Severe Effect	C-Fair	D-Severe Effect	A-Excellent
Chocolate Syrup	Excellent	Excellent	A-Excellent	A-Excellent	N/A
Clorox® (Bleach)	Excellent	Severe Effect	D-Severe Effect	N/A	A-Excellent
Coffee	Excellent	Excellent	A-Excellent	N/A	N/A
Cyclohexanone	Excellent	Excellent	D-Severe Effect	D-Severe Effect	D-Severe Effect
Diesel Fuel	Excellent	Excellent	A-Excellent	A-Excellent	A-Excellent
Ethanol	Excellent	Excellent	A-Excellent	B-Good	N/A
Ethyl Acetate	Excellent	Excellent		D-Severe Effect	D-Severe Effect
Ethylene Glycol	Excellent	Good	A-Excellent	B-Good	A-Excellent
Fluorine	Severe Effect	Severe Effect	D-Severe Effect	C-Fair	A-Excellent
Fruit Juice	Excellent	Severe Effect	B-Good	N/A	A-Excellent
Gasoline (high-aromatic)	Excellent	Good	A-Excellent	A-Excellent	A-Excellent
"Gasoline, leaded, ref."	Excellent	Excellent	B-Good	A-Excellent	A-Excellent
"Gasoline, unleaded"	Excellent	Excellent	C-Fair	A-Excellent	A-Excellent
Grape Juice	Excellent	Excellent	N/A	N/A	A-Excellent
Honey	Excellent	Excellent	A-Excellent	A-Excellent	A-Excellent
Hydrocyanic Acid	Good	Good	C-Fair	N/A	A-Excellent
• •	Severe Effect	Severe Effect	B-Good	A-Excellent	A-Excellent
Hydrogen Peroxide 100%		Excellent			
"Jet Fuel (JP3, JP4, JP5)"	Fair		A-Excellent	A-Excellent	B-Good A-Excellent
Kerosene Magnesium Chloride	Excellent	Excellent	B-Good	D-Severe Effect	A-Excellent A-Excellent
Magnesium Chloride	Excellent	Good	A-Excellent	A-Excellent	
Methanol (Methyl Alcohol)	Good	Excellent	A-Excellent	B-Good	A-Excellent
Methyl Ethyl Ketone	Excellent	Fair	B-Good	D-Severe Effect	D-Severe Effect
Milk	Excellent	Excellent	B-Good	A-Excellent	A-Excellent
Motor oil	Excellent	Good	A-Excellent	A-Excellent	B-Good
Nitric Acid (Concentrated)	Severe Effect	Severe Effect	D-Severe Effect	C-Fair	A-Excellent
Ozone	Severe Effect	Fair	B-Good	A-Excellent	A-Excellent
Phenol (10%)	Severe Effect	Good	B-Good	B-Good	A-Excellent
Rum	Excellent	Excellent	A-Excellent	N/A	N/A
Sea Water	Excellent	Excellent	A-Excellent	A-Excellent	A-Excellent
Sodium Chloride	Excellent	Excellent	A-Excellent	A-Excellent	A-Excellent
Sodium Hydroxide (80%)	Fair	Severe Effect	A-Excellent	D-Severe Effect	A-Excellent
Sulfuric Acid (75-100%)	Severe Effect	N/A	C-Fair	D-Severe Effect	A-Excellent
Sulfuric Acid (cold concentrated)	Severe Effect	N/A	A-Excellent	N/A	A-Excellent
Sulfuric Acid (hot concentrated)	Severe Effect	N/A	D-Severe Effect	D-Severe Effect	C-Fair
Tetrahydrofuran	Excellent	Excellent	C-Fair	D-Severe Effect	B-Good
Toluene (Toluol)	Excellent	Fair	C-Fair	D-Severe Effect	A-Excellent
Trichloroethylene	Fair	Severe Effect	C-Fair	N/A	B-Good
Urine	Good	Excellent	A-Excellent	N/A	A-Excellent
Water:Deionized	Excellent	N/A	A-Excellent	N/A	A-Excellent
Water:Delonized Water:Distilled	Excellent	Good	A-Excellent	A-Excellent	A-Excellent
Water:Fresh	Excellent	Excellent	A-Excellent	A-Excellent	A-Excellent
Water:Salt	Excellent	Excellent	A-Excellent	A-Excellent	A-Excellent
Whiskey & Wines	Excellent	Excellent	A-Excellent	A-Excellent	A-Excellent

Disclaimer: The data presented in this publication is for reference only. It was compiled primarily from outside sources provided by feedstock materials suppliers and resin manufacturers, and is offered to our customers as a means of comparing the characteristics of resins and materials used by KENT Systems at the time of publication. The particular conditions of your use and application of our products are beyond our control. Thus, it is imperative that you test our products in your specific application to determine their ultimate suitability. All information is provided without implied or expressed warranty or guarantee by KENT Systems, or the resin and feedstock manufacturers. KENT Systems. assumes no liability with respect to the accuracy or completeness of the information contained herein and none of the information provided constitutes a recommendation or endorsement of any kind by KENT Systems.

Phone: 970.593.3185 > Fax: 970.593.9684 > www.KentSystems.com



# Chimical Compatibility Information (Springs and O-Rings

CHEMICAL	BUNA-N	VITON A	EPDM	SILCONE	STAINLESS STEE
Acetic Acid	Fair	Good	Excellent	C-Fair	Severe Effect
Acetone	Severe Effect	Severe Effect	Excellent	D-Severe Effect	Excellent
Acetylene	Good	Excellent	Excellent	B-Good	Excellent
Alcohols:Amyl	Good	Excellent	Excellent	D-Severe Effect	Excellent
Alcohols:Benzyl	Severe Effect	Excellent	Good	N/A	Good
Alcohols:Butyl	Fair	Excellent	Excellent	B-Good	Excellent
Alcohols:Diacetone	Severe Effect	Severe Effect	Excellent	D-Severe Effect	Excellent
Alcohols:Ethyl	Fair	Excellent	Excellent	B-Good	Excellent
Alcohols:Hexyl	Excellent	Fair	Fair	B-Good	Excellent
Alcohols:Isobutyl	Good	Excellent	Excellent	A-Excellent	Excellent
Alcohols:Isopropyl	Good	Excellent	Excellent	A-Excellent	Good
Alcohols:Methyl	Excellent	Fair	Excellent	A-Excellent	Excellent
Alcohols:Octyl	Good	Good	Excellent	B-Good	Excellent
Alcohols:Propyl	Excellent	Excellent	Excellent	A-Excellent	Excellent
Aluminum Hydroxide	Excellent	Excellent	Excellent	N/A	Excellent
Antifreeze	Excellent	Excellent	Excellent	C-Fair	N/A
	Excellent				Good
Barium Sulfate		Excellent	Excellent	A-Excellent	
Benzene	Severe Effect	Excellent	Severe Effect	D-Severe Effect	Good
Benzoic Acid	Severe Effect	Excellent	Severe Effect	B-Good	Good
Brewery Slop	Excellent	Excellent	N/A	N/A	N/A
Butter	Excellent	Excellent	Excellent	B-Good	Fair
Buttermilk	Excellent	Excellent	Excellent	A-Excellent	Excellent
Cane Juice	Excellent	Excellent	Excellent	A-Excellent	Excellent
Carbon Dioxide (dry)	Excellent	Good	Good	B-Good	Excellent
Carbon Monoxide	Excellent	Excellent	Excellent	A-Excellent	Excellent
Carbon Tetrachloride	Severe Effect	Excellent	Severe Effect	D-Severe Effect	Good
Catsup	Excellent	Excellent	Excellent	N/A	Excellent
Chlorine (dry)	Good	Excellent	Excellent	D-Severe Effect	Excellent
Chlorine Water	Severe Effect	Excellent	Fair	D-Severe Effect	Fair
Chlorobenzene (Mono)	Severe Effect	Excellent	Severe Effect	D-Severe Effect	Excellent
Chocolate Syrup	Excellent	Excellent	Excellent	N/A	Excellent
Clorox® (Bleach)	Severe Effect	Excellent	Good	N/A	Excellent
Coffee	Excellent	Excellent	Excellent	A-Excellent	Excellent
Cyclohexanone	Severe Effect	Severe Effect	Good	D-Severe Effect	Excellent
Diesel Fuel	Excellent	Excellent	Severe Effect	D-Severe Effect	Excellent
Ethanol	Fair	Excellent	Excellent	B-Good	Excellent
Ethyl Acetate	Severe Effect	Severe Effect	Good	B-Good	Good
Ethylene Glycol	Excellent	Excellent	Excellent	A-Excellent	Good
Fluorine	Severe Effect	Fair	Excellent	D-Severe Effect	Fair
Fruit Juice	Excellent	Excellent	N/A	N/A	Excellent
Gasoline (high-aromatic)	Excellent	Excellent	Severe Effect	D-Severe Effect	Excellent
"Gasoline, leaded, ref."	Excellent	Excellent	Severe Effect	D-Severe Effect	Excellent
"Gasoline, unleaded"	Excellent	Excellent	Severe Effect	D-Severe Effect	Excellent
Grape Juice	Excellent	Excellent	Excellent	A-Excellent	Excellent
Honey	Excellent	Excellent	Excellent	A-Excellent	Excellent
Hydrocyanic Acid	Good	Excellent	Excellent	D-Severe Effect	Good
Hydrogen Peroxide 100%	Severe Effect	Excellent	Severe Effect	B-Good	Good
, ,	Excellent	Excellent	Severe Effect	D-Severe Effect	Excellent
"Jet Fuel (JP3, JP4, JP5)" Kerosene	Excellent	Excellent	Severe Effect	D-Severe Effect	Excellent
Magnesium Chloride	Excellent	Excellent	Excellent	A-Excellent	Severe Effect
Methanol (Methyl Alcohol)	Excellent	Fair Source Effort	Excellent	A-Excellent	Excellent
Methyl Ethyl Ketone	Severe Effect	Severe Effect	Excellent	D-Severe Effect	Excellent
Milk	Excellent	Excellent	Excellent	A-Excellent	Excellent
Motor oil	Excellent	N/A	Severe Effect	N/A	Excellent
Nitric Acid (Concentrated)	Severe Effect	Excellent	Severe Effect	D-Severe Effect	Excellent
Ozone	Severe Effect	Excellent	Excellent	A-Excellent	Good
Phenol (10%)	Severe Effect	Excellent	Good	D-Severe Effect	Good
Rum	Excellent	Excellent	Excellent	A-Excellent	Excellent
Sea Water	Excellent	Excellent	Excellent	A-Excellent	Fair
Sodium Chloride	Excellent	Excellent	Excellent	A-Excellent	Good
Sodium Hydroxide (80%)	Severe Effect	Severe Effect	Good	A-Excellent	Fair
Sulfuric Acid (75-100%)	Fair	Excellent	Good	D-Severe Effect	Fair
Sulfuric Acid (cold concentrated)	Severe Effect	Good	Fair	D-Severe Effect	Fair
Sulfuric Acid (hot concentrated)	Severe Effect	Excellent	Severe Effect	D-Severe Effect	Severe Effect
Tetrahydrofuran	Severe Effect	Severe Effect	Severe Effect	D-Severe Effect	Excellent
Toluene (Toluol)	Severe Effect	Fair	Severe Effect	D-Severe Effect	Excellent
Trichloroethylene	Severe Effect	Excellent	Severe Effect	D-Severe Effect	Good
Urine	Excellent	Excellent	Excellent	N/A	Excellent
Water:Deionized	Excellent	Excellent	Excellent	N/A	Excellent
Water:Distilled	Excellent	Excellent	Excellent	C-Fair	Excellent
Water:Fresh	Excellent	Excellent	Excellent	B-Good	Excellent
Water:Salt	Excellent	Excellent	Excellent	B-Good	Good
Whiskey & Wines	Excellent	Excellent	Excellent	A-Excellent	Excellent

Disclaimer: The data presented in this publication is for reference only. It was compiled primarily from outside sources provided by feedstock materials suppliers and resin manufacturers, and is offered to our customers as a means of comparing the characteristics of resins and materials used by KENT Systems at the time of publication. The particular conditions of your use and application of our products are beyond our control. Thus, it is imperative that you test our products in your specific application to determine their ultimate suitability. All information is provided without implied or expressed warranty or guarantee by KENT Systems, or the resin and feedstock manufacturers. KENT Systems. assumes no liability with respect to the accuracy or completeness of the information contained herein and none of the information provided constitutes a recommendation or endorsement of any kind by KENT Systems.

Phone: 970.593.3185 > Fax: 970.593.9684 > www.KentSystems.com